

# LOW CURRENT CLAMP METER

## Specifications

- ✓ Auto power off
- ✓ Data Hold Function
- ✓ Peak Hold Function
- ✓ One touch auto zero
- ✓ Low battery indicator
- ✓ Protective hand guard
- ✓ Relative measurement
- ✓ 50 hrs in use battery life
- ✓ Large 4 digit LCD display
- ✓ Resistance measurement.
- ✓ Soft carrying deluxe pouch
- ✓ One rotary switch operation
- ✓ 2 readings per second sampling
- ✓ Test leads and batteries included
- ✓ Continuity check with audible indicator
- ✓ Clamp opens up to 1/2 inch (12.5 mm)
- ✓ Small jaw: 300x13.4mm
- ✓ AC/DC Voltage measurement up to 600 Volt
- ✓ AC/DC current measurement from 0.001 up to 100 A.

**\$317.39**  
inc gst  
**EL001CM100**



180 g



## Kit Includes

- CM100
- Soft Pouch
- 2 x 1.3 m test probes
- Operation Manual Manual.
- 2 x 1.5 V AAA alkaline battery

The CM100 low current clamp meter is designed to accurately measure current, current leaks (parasitic draws down to 1mA) and electrical loads from 1mA to 100 amp AC/DC and voltages from 0 to 600 AC/DC. The CM100 can be used on electric motors, fuel pumps, charging systems, electrical circuits, etc

The small diameter (1/2 inch or 13mm) and narrow jaw makes it ideal for use in confined spaces and on small gauge wires. Other features include up to 600 volt AC/DC voltage, resistance measurement functions, audible continuity test, display hold and peak detector

[www.OLCT.co](http://www.OLCT.co)

Order Online  
[www.olct.co](http://www.olct.co)

Email Order  
[info@olct.co](mailto:info@olct.co)

Phone Order  
0466 909 653

Fax Order  
07 3041 3232

